

Safety Data Sheet: Bronzeseal laquer

Section 1: Identification

Product Name:	Bronzeseal
Proprietary Name:	Permalac AE
Manufacturer's Name:	Peacock Laboratories
Address	1901 S. 54th Street
City, State, Zip	Philadelphia, PA, 19143
Phone Number	215 729 4400
Emergency Contact	215 729 4400
Chemtrec	800 424 9300

Recommended Use: An exterior grade, non- yellowing, clear acrylic lacquer for the protection of metal, wood and masonry.

Section 2: Hazards Identification

Routes of Exposure: Inhalation, eye, skin

Signs and Symptoms of Exposure: High vapor concentrations may produce narcosis or anesthetic effect leading to death. Causes nose and throat irritation. Causes eye irritation. Causes skin irritations.

Medical Conditions Generally Aggravated by Exposure: Repeated and prolonged overexposure to solvents could cause permanent brain and nervous system damage. Intentional misuse by deliberately concentrating & inhaling contents may be harmful or fatal.

Hazard Rating: Health 2, Flammability 3, Reactivity 1
(Scale: 4B-Extreme, 3-High, 2BModerate, 1-Slight, 0-Insignificant)

Section3: Composition

	CAS Number	Weight %	Hazardous?
Toluene:	108-88-3	< 35%	Yes
Xylene	1330-20-07	< 35%	Yes
Propane	74-98-6	< 4%	Yes
Isobutene	75-28-5	< 2%	Yes
Acrylic Resin		3%	No

Section 4: First Aid Measures

Inhalation: Remove to fresh air, restore breathing. Consult a physician.

Skin Contact: Flush with water then wash skin thoroughly with soap and water while removing contaminated clothing. Consult a physician.

Eye Contact: Remove contact lenses flush immediately with large amounts of water for at least 15 minutes. Consult a physician.

Ingestion: DO NOT INDUCE VOMITING. Get medical attention immediately If vomiting occurs, keep head below hips to prevent aspiration into lungs.

Section 5: Fire Fighting Procedures

Flammable liquid and vapor. Vapors may migrate to ignition source and cause flash fire. Isolate from heat, sparks, electrical equipment, appliances, pilot lights, flames and other sources of ignition.

Flash Point: Toluene 43 F, Xylene 81F(closed cup)

Flammable Limits in Air % by Volume: Toluene lower limit 1.2%, upper limit 7%

Xylene lower limit 1.9%, upper limit 12.3%

Extinguisher Media: Dry chemical, carbon dioxide, or foam

Special Fire Fighting Procedures: Use NIOSH/MSHA approved gas mask for firefighting personnel. Water may be used to cool containers. If water is used fog nozzles are preferred.

Section 6: Accidental Release Measures

Ventilate area of leak or spill. Remove all sources of ignition. Contain and recover liquid when possible. Use non sparking tools and equipment. In case of spillage absorb with inert material (such as vermiculite, dry sand, or earth) and place in a waste chemical container and dispose of in accordance regulations of EPA and other local, state, and federal authorities. . Do not use combustible materials such as saw dust. Do not flush to sewer.

If a leak or spill has not ignited, use water spray to disperse the vapors, to protect personnel attempting to stop leak, and to flush spills away from exposures. US regulations require reporting spills and releases to water, soil and water in excess of reportable quantities.

Section 7: Handling & Storage

Store in a cool, dry well-ventilated location, away from heat, sparks and open flame. All equipment used when handling this product must be grounded. Empty containers may retain hazardous properties and can be dangerous. Avoid prolonged skin contact. Do not breath spray mist. .

Waste disposal methods (Consult federal, state, and local regulations): Place in closed containers.

Dispose of product in accordance with local, country, state, and federal regulations.

Section 8: Exposure Controls/Personal Protection

Engineering Controls

Both local exhaust and good general room ventilation must be provided not only to control exposure but also to prevent formation of flammable mixtures.

Personal Protection

Inhalation: A respiratory protection program that meets OSHA's 29 CFR 1910.134 or ANSI Z88.2 requirements must be followed whenever workplace conditions warrant respirator use.

Skin: Wear chemical resistant gloves such as: Butyl rubber, Nitrile or Teflon. Depending on the conditions of use, protective gloves, apron, boots, head and face protection should be worn. The equipment must be cleaned thoroughly after each use.

Eye: Use splash goggles when eye contact due to splashing or spraying liquid is possible.

Section 9: Physical & Chemical Properties Appearance

and Odor: Clear liquid with sweet odor. Boiling Point: N/A

Specific Gravity (water=1): N/A

Vapor Pressure (mm Hg): Acetone 181, T-BAc 34 Vapor

Density (Air=1): N/A, Is heavier than air. Solubility in

Water: Slight Reactivity in Water: None Melting Point:

N/A

VOC:<720 g/l

Volatile (Weight %): 97%

% Solids= 3%

The above data are approximate or typical values and should not be used for precise design purposes.

Section 10: Stability & Reactivity

Stability: Stable

Incompatibility (Materials to Avoid): Plastics, acids, alkalis, nitrates, and strong oxidizing agents. Avoid contact with heat, flames and sparks.

Hazardous Decomposition Products: Acetone and TBAc both generate carbon dioxide and Carbon monoxide upon thermal decomposition.

Hazardous Polymerization: Will not occur under normal conditions.

Conditions to Avoid: Heat, flames, ignition sources and incompatibles.

Section 11: Toxicological Information

Toluene:

Routes of Entry: Absorbed through skin. Dermal contact. Eye contact. Inhalation. Ingestion.

Toxicity to Animals: WARNING: THE LC50 VALUES HEREUNDER ARE ESTIMATED ON THE BASIS OF A 4-HOUR EXPOSURE. Acute oral toxicity (LD50): 636 mg/kg [Rat]. Acute dermal toxicity (LD50): 14100 mg/kg [Rabbit]. Acute toxicity of the vapor (LC50): 440 24 hours [Mouse].

Chronic Effects on Humans: CARCINOGENIC EFFECTS: A4 (Not classifiable for human or animal.) by ACGIH, 3 (Not classifiable for human.) by IARC.

May cause damage to the following organs: blood, kidneys, the nervous system, liver, brain, central nervous system (CNS).

Other Toxic Effects on Humans: Hazardous in case of skin contact (irritant), of ingestion, of inhalation. Slightly hazardous in case of skin contact (permeator).

Special Remarks on Toxicity to Animals: Lowest Published Lethal Dose: LDL [Human] - Route: Oral; Dose: 50 mg/kg LCL [Rabbit] - Route: Inhalation; Dose: 55000 ppm/40min

Special Remarks on Chronic Effects on Humans: Detected in maternal milk in human. Passes through the placental barrier in human. Embryotoxic and/or foetotoxic in animal.

May cause adverse reproductive effects and birth defects (teratogenic). May affect genetic material (mutagenic)

Xylene:

Acute Oral Toxicity:

Low toxicity: LD50 >2000 mg/kg, Rat

Aspiration into lungs when swallowed or vomited may cause chemical pneumonitis which can be fatal.

Acute Dermal Toxicity: Low toxicity: LD50 >2000 mg/kg,

Rabbit Acute Inhalation Toxicity: Low toxicity: LC50 >20mg/l /4 hours, Rat

High concentrations may cause central nervous system depression resulting in headaches, dizziness and nausea; continued inhalation may result in unconsciousness and/or death.

Skin Irritation: Irritating to skin.

Eye Irritation: Moderately irritating to eyes (but insufficient to classify).

Respiratory Irritation: Inhalation of vapours or mists may cause irritation to the respiratory system.

Sensitisation: Not a skin sensitiser.

Mutagenicity: Not mutagenic.

Reproductive Toxicity: Does not impair fertility

Carcinogenicity: Mixed xylenes contain ethylbenzene, which has shown limited evidence of a carcinogenic effect.

Repeated Dose Toxicity: Central nervous system: repeated exposure affects the nervous system. Effects were seen at high doses only.

Respiratory system: repeated exposure affects the respiratory system. Effects were seen at high doses only.

Visual system: may cause decreased colour perception. These subtle changes have not been found to lead to functional colour vision deficits.

Auditory system: prolonged and repeated exposures to high concentrations have resulted in hearing loss in rats. Solvent abuse and noise interaction in the work environment may cause hearing loss.

Additional Information: Exposure to very high concentrations of similar materials has been associated with irregular heart rhythms and cardiac arrest.

Section 12: Ecological Information

Mobility: Spillages may penetrate the soil causing ground water contamination. This material may accumulate in sediments.

Persistence and degradability: No data available

Bioaccumulative potential: Potentially bioaccumulate.

Aquatic toxicity: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Spills may form a film on water surfaces causing physical damage to organisms. Oxygen transfer could also be impaired.

Section 13: Disposal Considerations

Product disposal: Dispose of in accordance with all applicable federal, state, and local regulations. This product may produce hazardous vapors in a closed disposal container creating a dangerous environment. Refer to "40 CFR Protection of Environmental Protection Agency" before disposing of any chemicals. Do not flush to sanitary sewer or waterway.

SECTION 14: TRANSPORT INFORMATION

Proper Shipping Name: Paint

ID No: UN 1263

Hazard Class: 3

PG: II

Section 15: Regulatory Information

OSHA Hazards

Flammable liquid, Toxic by inhalation.

SARA 302 Components: SARA 302: No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313 Components: SARA 313: This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

SARA 311/312 Hazards: Fire Hazard, Acute Health Hazard

California Prop. 65 Components: This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

SECTION 16: OTHER INFORMATION

Date of last revision: 7/17/2013

Disclaimer: The above information in this M.S.D.S. was obtained from sources which we believe are reliable and correct, but does not purport to be inclusive and shall be used only as a guide. The information is provided without any representation or warranty expressed or implied regarding accuracy or correctness. The conditions or methods of handling, storage, use and disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, Peacock Laboratories, Inc. and its employees do not assume responsibility and expressly disclaim liability for loss, damage, or expense arising out of, or in any way connected with, the handling, storage, use or disposal of the product.